



LOADS ON PIT FLOOR

LOAD ON BUFFERS	4250 LBS.
LOAD ON JACK	4000 LBS.

NOTE:

THE MINIMUM FLOOR TO FLOOR TRAVEL FOR FRONT/REAR AND FRONT/SIDE OPENING ELEVATORS IS 2'-0"

NOTES:

- AMONG OUR MANY SPECIALTIES ARE CUSTOM SIZES AND CUSTOM CONFIGURATIONS; CONSULT OUR ENGINEERING STAFF FOR "OTHER THAN STANDARD" APPLICATIONS.
- DUE TO OUR POLICY OF CONTINUOUS IMPROVEMENT AND EVOLVING CODE REQUIREMENTS, WE RESERVE THE RIGHT TO ALTER OR AMEND THESE DETAILS AND, AS SUCH, THEY DO NOT FORM PART OF ANY CONTRACT. CONTACT OUR ENGINEERING STAFF FOR APPLICATION DRAWINGS SPECIFIC TO YOUR PROJECT PRIOR TO COMMENCING CONSTRUCTION.



HOISTWAY ELEVATION
FOR MODELS
CMR-450, CMR-750, I-2000
RESIDENTIAL ELEVATORS

DATE: 08-08-01

FILE NAME: ELEVAT